

CO Tracer

Carbon Monoxide Transmitter



Figure 1: CO Tracer

FEATURES

- Compact
- Inexpensive
- User selectable ranges
- IP65 enclosure
- Reverse voltage protection and temperature compensation

APPLICATIONS

- OXYGEN AND NITROGEN GENERATORS
- GAS MANUFACTURERS
- HEAT TREATING AND BRIGHT ANNEALING
- MEDICAL BREATHING

The CO Tracer

4 – 20 mA Loop Powered two wire CO Transmitter

The Model CO Tracer is simple, accurate and very economic measurement of CO in the ppm levels.

Typical range is 0-50 ppm. For special ranges please consult factory

The CO Tracer uses a special electro chemical cell to measure the CO concentration. The sensor meets the industrial requirements for accuracy, sensitivity, easy to use and has a long operating life.

The sensor comes fully calibrated and requires no calibration for two years. After that period, it can be calibrated on a calibration gas. The sensor life is good to 5000ppm hrs.

CO Tracer

Carbon Monoxide Transmitter



Technical Information

Measurement Ranges	0-50ppm CO For special ranges Consult the factory
Calibration	Use a known CO calibration gas that is NIST traceable
Response Time	90 % FSD at 20°C < 30 sec 90%
Load	typ. 470 Ohm at 18Vdc max. 700 Ohm
Pressure	0.1-1 bar
Supply Voltage	10 – 35 VDC reverse voltage protection up to 40VDC
Sensor	Micro-Fuel Cell
Dimensions	80 x 75 x 55 (B x H x T (mm))
Weight	0.6 lb.
Signal Output	4-20mA/DC
Operating Temperature	0°C to +50 °C
Warmup Time	2 minutes
Sample Flow Rate	1-3 scfh
Enclosure Rating	IP65 , Aluminum
Process Connection	¼" tube
Accuracy	+/- 2% FSD T= const. +/- 5% FSD 0>T>50°C